



SPECIFICATIONS	531	561	591	631
BEAM	2.40m	2.45m	2.50m	2.50m
DEPTH	1.40m	1.50m	1.55m	1.55m
LENGTH	5.35m	5.65m	5.95m	6.35m
WEIGHT - BOAT ONLY	620kg	660kg	750kg	780kg
воттом	4.00m	4.00mm	4.00mm	4.00m
SIDES	4.00m	4.00mm	4.00mm	4.00m
PEOPLE	5	6	6	7
MAX HP	115hp	150hp	150hp	175hp
SHAFT	X Long	X Long	X Long	X Long

STANDARD FEATURES

- 4mm 5083 high tensile Keel Sheets
- 4mm 5052 Side Sheets
- · 4mm Bulkheads and frames fully welded to hull not floating
- Soft Rider transom with twin boarding platforms
- Fully welded gunnels and side decks
- Extruded Side Decks
- Enclosed rear transom with twin hatches
- Large aluminium anchor well
- 32mm Bow & Rear Rails
- Heavy-duty bow sprit with double rollers and rope keepers
- Full carpeted floor
- Cast alloy bollards x 3
- Transducer brackets x 2
- Australian Standards Approved underfloor foam floatation
- Large 800mm centre console with shelf and folding windscreen
- Rod holders x 4

- Large side pockets
- · Heavy-duty dive boarding ladder
- Hydraulic steering system
- Sports spoke steering wheel
- Helm seat box with flip backrest
- 150L underfloor fuel tank with sender
- 175L underfloor fuel tank with sender (561)
- 200L underfloor fuel tank with sender (591)
- 250L underfloor fuel tank with sender (631)
- Marine level tinned wiring loom
- 5 gang switch panel with 12V outlet
- LED nav lights & anchor light
- Bilge pump
- White paint
- Graphics
- Outer edge hull reverse chine

OPTIONAL FEATURES

- Transom door (531, 561, 591, 631)
- Two tone paint (531, 561, 591, 631)
- Bait board with bait tank (531, 561, 591, 631)
- Plumbing of bait tank in bait board(531, 561, 591, 631)
- Kill tank (531, 561, 591, 631)
- T-top (531, 561, 591, 631)
- Checker plate welded self-dreain floor (531, 561, 591, 631)
- Alloy rod holders rivited in (531, 561, 591, 631)
- Alloy rod holders welded in (531, 561, 591, 631)
- Hydrailic steering upgrade (531)
- 5mm 5083 high tensile bottom sheets and transom (591, 631)